

# Hilbert-Huang Transform:

A method for analyzing nonlinear and nonstationary data

presented by:

**Norden Huang** 

NASA Medical Technology Summit

February 12, 2003 • Pasadena, CA



- Design motivation and concept inception
- Technology description
- Market potential
- Status of development
- Technology details and results
- Summary
- Contact info
- Acknowledgements
- Q&A





# Problems result from characteristics of data:

- Insufficient sample size
- Nonstationary data
- Nonlinear data





#### **Prior art:**

- Wavelet analysis, Wigner-Ville transforms, Fourier analysis
- Singular spectral analysis, nonlinear phase plane analysis

#### **Each has limitations**

Result is inaccurate interpretation of underlying physics





# The basic problem in analyzing data:

- All existing methods are for either linear or stationary data or they assume deterministic processes.
- Most actual data are nonlinear, nonstationary, and stochastic.





#### Goal:

 Develop a means of accurately analyzing nonlinear, nonstationary data





#### **Basic concept:**

- Any applied mathematics method that analyzes nonlinear, nonstationary data has to be adaptive.
- To be effective and rich in information, any basis has to involve a finite and often small number of discrete modes that retain the intrinsic properties of the original data.





#### Technical goals of data analysis:

- To define local time scale or frequency
- To define local energy density
- To define joint frequency-energy distribution





#### **Method:**

- Empirical Mode Decomposition method extracts intrinsic mode functions (IMFs), (i.e., oscillation modes within data) which still retain intrinsic characteristics of the data
- Hilbert-Huang Transform (HHT) converts IMFs into local energy and instantaneous frequencies as a base for the full energyfrequency-time distribution of data (i.e., Hilbert spectrum)
- Physical signal is filtered by reconstructing signal from selected IMFs or IMF sections

#### **Technology Description Comparisons: Fourier, Hilbert & Wavelet** Data Fourier 100 50 0, 0 -1 0.01 500 0.005 1000 200 400 600 800 1000 Hilbert Wavelet 0.2 0. 0.01 0.01 500 500 0.005 0.005 1000 1000



#### **Results:**

- An adaptive basis to filter signal
- Frequency defined as a function of time by differentiation rather than convolution analysis
- Sharp identification of embedded structures
- A more simple and revealing interpretation than prior methods





# **Key Considerations**



- An efficient, adaptive, user-friendly set of algorithms
- Capable of analyzing nonlinear and nonstationary signals as well as linear and stationary signals





# **Key Considerations**

- Improves accuracy by using an adaptive basis to preserve intrinsic properties of data
- Yields results with more physical meaning and a different perspective than existing tools
- Useful in analyzing a variety of physiological signals as well as many other signals from nonlinear and nonstationary processes





# **Market Potential**

#### **Benefits**


#### **Precision:**

- More precise time-frequency representation of signal data than with "Fourier-type" methods
- **Sharper filter performance than** provided by "Fourier-type" methods



# Flexibility:

- Designed for processing nonlinear and nonstationary signals
- Flexible enough to analyze any data (linear or nonlinear) and stationary or nonstationary signals



# Market Potential **Benefits**

#### **Accuracy:**

- Preserves intrinsic properties of data
- Offers a microscopic view of data not limited by the uncertainty principle
- Does not impose a priori assumptions on data, as in Fourier methods (i.e., that assume linear and stationary data)



#### **Easy implementation:**

 Easy and inexpensive to implement in software or hardware

#### **Real-time operation:**

 Operates and yields physically meaningful results in real time





#### Market Potential

#### **Benefits**

#### **Multifunctionality:**

- **Generates IMFs through an adaptive** algorithm from a data set with which other methods fail
- **Examines previously unattainable** results for aiding diagnosis
- Provides new, quantitative measurements that enhance understanding of underlying physiological phenomena



# **Applications**



- Analyzing and correcting satellite data
- Analyzing data to understand underlying phenomena
- Fusing data from multi-sensors

#### Other government entities:

- DOT (seismic load and nondestructive testing)
- FBI (speech analysis and speaker identification)
- U.S. Navy (shock loading and nondestructive testing)
- NIST (machine health monitoring)



#### **Commercial:**

- **Predicting incipient failure of machinery**
- Analyzing sound waves, electromagnetic waves, heat conduction/convection, and mechanical vibrations
- Interpreting nonstationary signals

#### **Medical**







- Blood pressure
- Heart pulse interval
- Heart rate
- Plethysmogram signals
- Electroencephalogram (EEG) signals
- Temperature signals
- Blood oxygen levels
- Speech (i.e., soundwaves)
- Electrocardiogram (ECG)





#### **Noise filtering:**

- Reducing noise
- Increasing signal clarity

#### Research:

 Studying the effect of one variable on another to get a deeper understanding of the underlying physiological phenomenon





# Diagnosis of an abnormal condition or disease:

- Sleep apnea
- Neurological disorders (e.g., epilepsy and Parkinson's disease)

#### In vitro studies:

- Current flow across membranes (i.e., patch clamping)
- Fluorescence in confocal microscopy
- Analysis of spectroscopic signals





- Heart rate
- Blood pressure
- Other physiological functions

Deriving an analytical function representative of a biological phenomenon





#### **Drug discovery:**

- Assessing protein structure
- Examining protein-protein interactions

Tissue engineering and design





- Implemented and tested in the following medical applications:
  - » Blood pressure data from the pulmonary artery of a rat
  - » Pulmonary blood pressure signals in response to step changes in oxygen concentration in the breathing gas
  - » Heart pulse interval comparing sleep apnea condition to a non-apnea condition
  - » Epileptic seizure heart pulse data
- Figures summarizing results can be found in U.S. Patent 6,381,559
- Data and additional results are proprietary and confidential







# **Intellectual Property Protection**

#### **Issued patents:**

- U.S. Patent No. 6,311,130
   Computer Implemented Empirical Mode Decomposition Method, Apparatus, and Article of Manufacture Utilizing
   Curvature (issued 10/01)
- U.S. Patent No. 5,983,162
   Computer Implemented Empirical Mode Decomposition Method, Apparatus, and Article of Manufacture (issued 9/99)

#### **Copyright:**

 Computer Implemented Empirical Mode Decomposition Method, Apparatus, and Article of Manufacture





# **Intellectual Property Protection**

#### **Pending patents:**

- U.S. App. No. 09/082,523
   Extrema Continuation in Part Allowed (filed 5/98)
- U.S. App. No. 09/282,424
   Implemented Empirical Mode
   Decomposition Method, Apparatus,
   and Article of Manufacture for
   Analyzing Biological Signals and
   Performing Curve Fitting (filed 3/99)






# **Intellectual Property Protection**

#### **Pending patents: (cont)**

- U.S. App. No. 09/729,138
   Three Dimensional Empirical Mode Decomposition Analysis Apparatus and Method (filed 11/00, inventor Per Gloersen)
- U.S. App. No. 10/073,957
   Application of HHT for Acoustical Signal Analysis: With Special Emphasis on Speech Analysis, Synthesis, Identification, Enhancement, and Machine Health Monitoring (filed 2/02)

#### Technology Details and Results

# **Speech Analysis Example**



#### **Technology Details and Results** Speech Analysis Example Narrowband Spectrogram: Hallo 1024 Wideban Wideband Spectrogram : Hallo 64 3500 3000 2500 2500 £ 2000 2000 1500 1500 1000 -1000 500 500 0.25 0.3 Hilbert Spectrum : Hello Time: second 4000 Wavelet Spectrum: Hello 5:2048 4000 3500 3000 3000 -2500 2500 € 2000 2000 1500 1500 1000 1000 500 -31 0.1 0.15 Time: second Time: second



# **Speech Analysis Example**

#### **Benefits in sound enhancement:**

- Fourier filter is linear and stationary;
   it works in frequency domain
- Fourier filter takes away harmonics and dulls sharp corners of all fundamentals
- EMD filter is nonlinear and intermittent; it works in time domain
- EMD filter removes unwanted noise of short periods and leaves fundamentals unchanged








# **Ongoing Work**



- Universities
- Government laboratories


#### **Conferences:**

- SIAM (Society for Industrial and Applied Mathematics) and CAIMS (Canadian Applied and Industrial Mathematics Society) Joint Annual Meeting, 2003; Montreal Canada
- First International Symposium on HHT Developments and Applications, 2003; Taipei, Taiwan



**Summary** 

- Licensing and partnering opportunity
- Enabling technology with significant commercial potential in medicine
- Significant benefits
  - » Precision, flexibility, accuracy, easy implementation, real-time operation, and multifunctionality



**Summary** 

- Numerous application possibilities
  - Extracting intrinsic mode functions, aiding in diagnosis, gaining understanding of physiological phenomena
- Intellectual property protected
- Concepts demonstrated in medical applications



For more information, please contact:

#### **Nicole Martel**


• Phone: (203) 321-1923

• E-mail: nmartel@fuentek.com





- **Inventor Norden Huang**
- **Member of National Academy of Engineering**
- Presentations made at numerous universities and other NASA field centers
- Papers published
  - » Proceedings of the Royal Society of London
  - » Proceedings of the National Academy of **Sciences**
  - » Annual Review of Fluid Mechanics
  - » Bulletin of Seismological Society of **America**



# Acknowledgements

- Awards
  - » NASA Exceptional Space Act, 1998
  - » Federal Government Technology Leadership Award, 1999
  - » Federal Laboratory Consortium Technology Development Award, 2001
  - » R&D 100 Award, 2001